



Ball Valve S4 3W T-ball DN40 PVC grey PVCu solvent socket d50 metric PN3 EPDM tpe EO510 ECO 230VAC Solar

Product code: 120651

Selection:

Ball Valve S4 3W T-ball DN40 PVC grey PVCu solvent socket d50 metric PN3 EPDM tpe EO510 ECO 230VA...

Please login to see the price.

 The dispatch takes place within 5 working days.

DESCRIPTION TECHNICAL DETAILS DOWNLOADS

product Ball Valve	serie S4	type 3W
characteristic T-ball	nominal diameter DN40	material PVC
color grey	pipe-connection-type PVCu solvent socket ends	dimension d50
Standard metric	pressure PN3	material O-ring EPDM
material seat-sealing tpe	actuators_controll EO	actuators type 510
additional characteristic ECO 230VAC	Spezial type solar	

DESCRIPTION TECHNICAL DETAILS DOWNLOADS

TECHNICAL DATA

• Eco 230V AC manipulation time: 90° 22 sec • Optical position indication • Manual override • Compact construction, T-ball • Chlorine and sea water resistant (corrosion-free) • Protection code IP 65 (EO510) • Electr. position indication • CE marking • On-time: 60%/max. 20 min.

PATENTED PRESSURE VENTING SYSTEM

Small drill holes in the T-ball and in the pressure ring – ideal for pool solar application

APPLICATION

• In combination with all pool solar absorber systems (EPDM, PE, PP) and pool solar control possible